

DTK-120SRD

Series Connected Surge Protector with Dry Contacts



Product Features

- Series design for fast response and best protection
- Compact design fits in a variety of control panels
- Suitable for use on circuit breakers rated at 10kA AIC
- Multi-stage hybrid circuit design
- UL1283 EMI/RFI filtering
- LED indicates protection status
- Form C Dry Contact circuit

Application

- Fire Alarm Panels
- Control Panels
- 120VAC Single Phase Critical Loads
- UL Listed Control Panels where UL Recognized Components are Required

Accessories

- DIN Rail Mounting Kit – Part Number DTK-DRK

DITEK's DTK-120SRD protects dedicated 120VAC power circuits that feed control panels and other critical equipment. The hybrid series design provides maximum critical load protection, and includes dry contacts for remote notification of surge protection status. EMI/RFI filtering ensures clean power for connected equipment.

Technical Specifications

Service Voltage:	120VAC Single Phase
MCOV:	150VAC
Protection Modes:	All modes – L-G, L-N, N-G
Voltage Protection Rating:	600V L-G, L-N, 1,000V N-G
Surge Current Rating:	50,000 Amps
Max. Continuous Current:	20 Amps
SCCR:	10kA
Nominal Discharge Current Rating (I_n):	10kA
Operation Frequency:	40Hz – 400Hz
EMI/RFI Filtering Attenuation:	Up to 35dB, 100kHz -100MHz

Mechanical Characteristics

Connection Method:	Hardwired, series configuration
Housing:	ABS
Operating Temperature:	-40°F - 185°F (-40°C - 85°C)
Maximum Humidity:	95% non-condensing
Dimensions:	6.87"L x 3.5W x 2.5"H (174050mm x 88.90mm x 63.50mm)
Weight:	12.16 oz (0.35kg)

Quality, Standards & Approval

Agency Approvals:	UL1449 4 th Edition, cUL, UL1283
SPD Type:	Type 2 Component Assembly
Standards Compliance:	IEEE C62.41.1 –2, IEEE C62.45
Warranty:	Ten Year Limited Warranty

Every precaution has been taken to ensure that this literature is accurate and complete. DITEK Corporation assumes no responsibility and disclaims all liability for damages resulting from the use of this information or for any errors or omissions.

