



## D300MT Series 300kA Modular Surge Protective Device

DITEK's D300MT Industrial Surge Protectors with integral disconnect are designed to provide professional-grade protection to AC power systems in the most demanding environments. Each model provides a high surge current rating to ensure long service life, and includes service assurance features that help alert building management of their current protection status so that managers can take action to maintain continued protection.



### Product Features

- 300,000 Amps per Phase surge current rating to meet new construction bid/spec requirements for facility-wide protection
- Visual LED End of Life Indicator
  - Green = 67 to 100% Life
  - Yellow = 34 to 66% Life
  - Red = 0 to 33% Life
- Surge counter with reset button
- Audible alarm with silence button
- Form C dry contacts for remote monitoring
- Phase loss indication
- EMI/RFI filtering
- Replaceable SPD module
- UL96A Lightning Protection Compliant
- Available in 5 voltage configurations, with up to 10 modes of protection
- UL98 Integral Disconnect Switch included

### Applications

- Service Entrance
- Distribution Panel

### Accessories

- Replacement SPD Module: See chart on page 2

### Technical Specifications

<b>Voltage Configurations:</b>	See Chart on Page 2
<b>Surge Current Rating:</b>	300,000A / Phase 150,000A / Mode
<b>SCCR:</b>	200,000A
<b>EMI/RFI Filtering:</b>	Up to -50dB 10kHz to 100Mhz
<b>Operating Frequency:</b>	50/60Hz

### Mechanical Specifications

<b>Connection Method:</b>	Mechanical Lugs 8 AWG – 1/0 AWG
<b>Housing:</b>	NEMA 4
<b>Operating Temperature:</b>	-40°F – 185°F (-40°C – 85°C)
<b>Maximum Humidity:</b>	95% non-condensing
<b>Dimensions:</b>	17.52" L X 12.98" W x 8.06" H (445 mm x 330 mm x 205 mm)
<b>Weight:</b>	27 lb (10.2 kg)

### Quality Standards & Approvals

<b>Certifications:</b>	UL1449 5 <sup>th</sup> Edition
<b>SPD Type:</b>	Type 1
<b>Warranty:</b>	10 Year Limited Warranty

Find us in

**MasterSpec**  
a product of The American Institute of Architects





## D300MT Series 300kA Modular Surge Protective Device

Part Number	Replacement SPD Module	Service Voltage	Service Configuration	MCOV	UL In Rating	Voltage Protection Rating (VPR)			
						L-G	L-L	L-N	N-G
<b>D300M-120/2401T</b>	D300M-240SM	120/240VAC	Split $\Phi$ (3W + G)	150V/276V	20kA	900V	1500V	900V	900V
<b>D300M-120/2083YT</b>	D300M-208YM	120/208VAC 127/220VAC	Three $\Phi$ Wye (4W + G)	150V/239V	20kA	900V	1500V	900V	900V
<b>D300M-277/4803YT</b>	D300M-480YM	277/480VAC 220/380VAC 230/400VAC 240/415VAC	Three $\Phi$ Wye (4W + G)	320V/552V	20kA	1200V	2500V	1200V	800V
<b>D300M-2403DT</b>	D300M-240DM	240VAC	Three $\Phi$ Delta (3W + G)	320V/320V	20kA	1200V	2500V	N/A	N/A
<b>D300M-4803DT</b>	D300M-480DM	480VAC	Three $\Phi$ Delta (3W + G)	552V/552V	20kA	1800V	4000V	N/A	N/A

