



DTK-2MHLPF Series

Modular Low Voltage Surge Protectors

DITEK's DTK-2MHLPF Series of low voltage surge protectors provide robust protection in a compact package. This series was designed for ease of installation, with convenient field-replaceable modules and a Snap-Track base system, allowing the installer to protect multiple circuits while utilizing a common ground point.



PRODUCT FEATURES

- Protects (2) low voltage circuit pairs per module
- Hybrid design utilizing TVS diode and GDT technologies
- Field-replaceable modular design
- 7 voltage configurations available to protect a wide variety of circuit types
- "WB" suffix added to module part number includes single position mounting base

APPLICATIONS

- SLC, IDC & PIV Circuits
- 4-20mA Current Loops
- Automation Control Circuits
- Telco Circuits

ACCESSORIES

- DTK-MB10 single mounting base (2 pairs)
- DTK-2MB 2-position mounting base (4 pairs)
- DTK-3MB 3-position mounting base (6 pairs)
- DTK-4MB 4-position mounting base (8 pairs)
- DTK-5MB 5-position mounting base (10 pairs)
- Test Module P/N DTK-2MHLPTM

TECHNICAL SPECIFICATIONS							
DTK-2MHLP	5F	12F	24F	36F	48F	75F	130F
Service Voltage:	5Vdc	12Vdc	24Vdc	36Vdc	48Vdc	75Vdc	130Vdc
MCOV:	6V	18V	33V	48V	64V	90V	140V
Clamping Voltage:	8V	22V	39V	57V	76V	108V	155V
Protection Modes:	Differential Mode (Line-Line) Common Mode (Line-Ground)						
Surge Current Rating:	20,000A						
Max. Continuous Current:	1 amp						
Failure Mode:	Open circuit						

DITEK Surge Protection, Largo, FL 33771 • Sales: 800-753-2345
 Diteksurgeprotection.com • SPS-100010-003 Rev 6 04/26





Every precaution has been taken to ensure that this is accurate and complete. DITEK Corporation assumes no responsibility and disclaims all liability for damages resulting from the use of this information or for any errors or omissions.



DTK-2MHLPF Series

Modular Low Voltage Surge Protectors



MECHANICAL SPECIFICATIONS	
Connection Method:	Screw terminals 30-12AWG
Housing:	ABS
Operating Temperature:	-40°F – 158°F (-40°C – 70°C)
Maximum Humidity:	95% non-condensing
Dimensions:	<p>DTK-2MHLPF with DTK-MB10 mounting base 3.25 in. L x 1.5 in. W x 2.65 in. H (83 mm x 38 mm x 67 mm)</p> <p>DTK-2MB 2-position mounting base 3.25 in. L x 3.0 in. W x 2.65 in. H (83 mm x 76 mm x 67 mm)</p> <p>DTK-3MB 3-position mounting base 3.25 in. L x 4.5 in. W x 2.65 in. H (83 mm x 114 mm x 67 mm)</p> <p>DTK-4MB 4-position mounting base 3.25 in. L x 6.0 in. W x 2.65 in. H (83 mm x 152 mm x 67 mm)</p> <p>DTK-5MB 5-position mounting base 3.25 in. L x 7.5 in. W x 2.65 in. H (83 mm x 191 mm x 67 mm)</p>
Weight:	4 oz (113g)

SAFETY STANDARDS AND CERTIFICATIONS	
Certifications:	UL 497B
Standards Compliance:	RoHS
Warranty:	10 Year Limited Warranty

DITEK Surge Protection, Largo, FL 33771 • Sales: 800-753-2345
 Diteksurgeprotection.com • SPS-100010-003 Rev 6 04/26



Every precaution has been taken to ensure that this is accurate and complete. DITEK Corporation assumes no responsibility and disclaims all liability for damages resulting from the use of this information or for any errors or omissions.