



DTK-8FF

8-Outlet Surge Protective Device

DITEK's DTK-8FF eight-outlet Surge Protective Device (SPD) protects AC power and telco/modem/fax lines. Its hybrid circuitry provides excellent point of use protection. Up to six transformers can be used at the same time, and EMI/RFI filtering provides extra protection for sensitive electronics.



PRODUCT FEATURES

- (8) 120vac outlets protected, up to six transformers
- Diagnostic LED indicates ground presence and suppressor function
- Automatic shutdown feature turns off power in case of suppressor overload
- 1 in / 2 out RJ11 telco protection included
- Mounting slots allow installation on wall or backboard

APPLICATIONS

- Audio/Video Equipment
- Access Control Panels
- Point of Use Appliances

TECHNICAL SPECIFICATIONS	
Service Voltage:	120Vac Single Φ
Surge Current Rating:	144,000A
Max. Continuous Current:	15 amps
Nominal Discharge Current Rating (I_n):	3kA
MCOV:	127V
Voltage Protection Rating (VPR):	400V Line-Ground 400V Neutral-Ground 330V Line-Neutral
Operating Frequency:	50/60Hz
Status Indication:	LED

DITEK Surge Protection, Largo, FL 33771 • Sales: 800-753-2345
Diteksurgeprotection.com • SPS-100026-001 Rev 11 05/26





DTK-8FF

8-Outlet Surge Protective Device

MECHANICAL SPECIFICATIONS	
Connection Method:	NEMA 5-15P 4-foot cord
Housing:	ABS
Operating Temperature:	32°F – 77°F (0°C – 25°C)
Maximum Humidity:	95% non-condensing
Dimensions:	10.5 in. L x 3.9 in. W x 1.4 in. H (267 mm x 99 mm x 36 mm)
Weight:	1.75 lbs. (0.79kg)

SAFETY STANDARDS AND CERTIFICATIONS	
Certifications:	UL 1449 4 th Edition Type 3 SPD CSA C22.2 No. 269.1-17, 2017-02
Standards Compliance:	RoHS
Warranty:	10 Year Limited Warranty

