

DTK-HVACKIT HVAC System Surge Protection Kit

DITEK's HVAC Surge Protection Kit is perfect for commercial and residential HVAC installers who want to provide an additional, valuable service to their customers. Power outages, surges and voltage transients can damage your heating and cooling system just like any other valuable electronic device. DITEK's top quality, superior performing products help prevent equipment loss during these damaging events



Product Features

DTK-120/240CM+: Condensing Unit Surge Protector

- > 120/240V single phase surge protective device
- NEMA 4X weatherproof enclosure
- Install and wire to the load side of the disconnect
- Parallel connection for easy installation
- Diagnostic LED indicates power, ground presence and surge protection status
- Automatically resets to handle multiple surge events

DTK-4LVLPLV: Thermostat Surge Protector

- 4-pair, 24V Surge Protection
- Install in series with the thermostat control wires at air handler
- Series connection, parallel function adds no resistance to loop circuits

Applications

Heating & Air Conditioning Systems

| Technical Specifications | | | |
|---|------------------------|-------------------|--|
| Part Number: | DTK-120/240CM+ | DTK-4LVLPLV | |
| Service Voltage: | 120/240VAC | 24V | |
| MCOV: | 150/320VAC | 38V | |
| Clamping Voltage: | N/A | 47V | |
| Protection Modes: | L-G, L-L | Common Mode (L-G) | |
| Voltage Protection Rating: | 700V L-G 1,200V L-L | N/A | |
| Surge Current Rating: | 50,000A | 2,000A | |
| SCCR: | 10,000A | N/A | |
| Nominal Discharge Current Rating (In): | 10kA | N/A | |
| Operation Frequency: | 50/60Hz | N/A | |

| Mechanical Specifications | | | |
|---------------------------|--|---|--|
| Connection Method: | 3/4" NPT Parallel Wired, 12 AWG | Hardwired terminals: 22 – 16 AWG | |
| Housing: | NEMA 4X | ABS | |
| Operating Temperature: | -31°F - 104°F (-35°C - 40°C) | -40°F - 158°F (-40°C - 70°C) | |
| Maximum Humidity: | 95% non-condensing | N/A | |
| Dimensions: | 3.5" L X 1.89" W X 3.4" H (88.9 mm x 48.3 mm x 86.4 mm) | 4.8 "L X 2.3" W X 1.5" H (122 mm X 58 mm X 35 mm) | |
| Weight: | 0.55 lb (25 kg) | 2.4 oz (68g) | |

| Quality Standards & Approvals | | | |
|-------------------------------|--------------------------|--------|--|
| Agency Approvals: | UL1449 Listed, cUL | UL497B | |
| SPD Type: | Type 1 SPD | N/A | |
| Warranty: | 10 Year Limited Warranty | | |







