

DTK-RM24EXTS

Rack Mount PoE Extender Surge Protector



DITEK's DTK-RM24EXTS is a 24-channel, 1U rack mount surge protector designed with state-of-the-art circuitry to provide superior protection for Power over Ethernet Extender circuits. It supports data speeds up to 10GbE, and provides surge protection grounding to remote devices when used with STP cabling. The DTK-RM24EXTS is ideal for installations using long range PoE extender equipment.

Product Features

- Hybrid design utilizing SAD and GDT technologies for optimal protection
- Robust 20kA per pair surge current rating
- Rapid-Replacement modular design allows modules to be swapped from front of device without removing from rack
- Complies with all IEEE Power over Ethernet standards
- UL497B Listed

Applications

Long Range PoE Extenders

Accessories

Mix and match rapid-replacement modules to protect Ethernet, PoE and PoE Extender circuits within the same rack mount housing

DTK-NETMS – For Ethernet & PoE Circuits
DTK-EXTMS – For PoE Extender Circuits

Technical Specifications			
Service Voltage:	<60V		
Protection Modes:	Common (All), Differential (All)		
Clamping Voltage:	Common Mode: 75V Differential Mode: 72V		
Surge Current Rating:	20kA / Pair		
Power Handling:	Up to 144 Watts		
Data Rate:	Up to 10GbE		

Mechanical Specifications			
Connection Method:	Shielded RJ45 Female In/Out		
Housing:	Galvanneal		
Operating Temperature:	-40°F – 158°F (-40°C – 70°C)		
Maximum Humidity:	95% non-condensing		
Dimensions:	19" L X 2.75" W x 1.75" H (483 mm x 70 mm x 45 mm)		
Weight:	4.35 lb (1.97 kg)		

Quality Standards & Approvals		
Certifications:	UL497B	
Standards Compliance:	CAT5e, EIA/TIA 568A, EIA/TIA 568B	
Warranty:	10 Year Limited Warranty	

IEEE PoE Standard	Wattage	Compatible
802.3af	15.4 W	Yes
802.3at	30 W	Yes
802.3bt Type 3	60 W	Yes
802.3bt Type 4	100 W	Yes







