

DITEK's DTK-RMAC12 is the perfect solution for today's rack-mounted servers, call systems, controllers, and CCTV equipment. The 1U rack configuration provides twelve surge protected AC outlets, with six on the front for convenience. The front-mounted on/off switch allows for emergency shutdowns, and diagnostic LEDs indicate electrical system and surge protection status.

Product Features

- (12) NEMA 5-15P surge protected outlets 6 on the front and 6 on the back
- EMI/RFI Noise Suppression
- LED indicator lights Power On, Surge Protection OK, Wiring Fault
- 15 Foot cord for installation convenience

Applications

- Rack Mounted Servers
- Call Systems
- Controllers
- **CCTV** Equipment

Technical Specifications	
Service Voltage:	110VAC – 120VAC
Protection Modes:	L-N, L-G, N-G
Surge Current Rating:	90,000A
Max. Continuous Current:	15A
Operation Frequency:	50/60Hz
EMI/RFI Noise Filtering:	58dB, 150kHz – 100MHz

Mechanical Specifications	
Dimensions:	19.0" L X 3.75" W X 1.75" H (483 mm X 95 mm X 45 mm)
Weight:	5.25 lb

Quality Standards & Approvals	
Agency Approvals:	UL1449 Recognized Component
SPD Type:	SPD Type 4
Warranty:	10 Year Limited Warranty



