

DTK-S "Snap-It" Series 66 Block Quick-Connect Surge Protectors

DITEK's "Snap-It" Series quick-connect surge protectors are designed specifically for Voice/Data professionals. The Snap-It provides both voltage and current limiting in addition to surge protection. Available in four different voltages, the DTK-S series makes digital line protection a "Snap!"



Product Features

- Quick connect module no bridge clips required
- > Each Snap-It protects one pair
- Field-replaceable, with built in diagnostic test points
- Self-resetting fuse on models with "A" suffix
- Models available for both current-limited, standard lines, and low capacitance digital lines

Applications

- Digital Voice/Data Systems
- Intercom Systems
- > Analog Phone Systems

Note

 Each 66 Block requires one gr and bar: DTK-SIGB

Technical Specifications				
DTK-	S14	S30	S50	S130
Service Voltage:	14V	30V	50V	130V
MCOV:	18V	38V	66V	175V
Clamping Voltage:	22V	47V	82V	204V
Protection Modes:	Tip-Ground, Ring-Ground			
Surge Current Rating:	1,000A	1,000A	3,500A	3,500A
Max. Continuous Current:	"-A" models 150mA "-B" models 2A			

Mechanical Specifications

Base Connection Method:	Press-to-Fit connection to 66 Block		
Housing:	High Impact Plastic		
Operating Temperature:	-40°F - 158°F (-40°C - 70°C)		
Maximum Humidity:	95% non-condensing		
Dimensions:	.3.24" L x .38" W x 1.56" H (82.3 mm x 9.6 mm x 39.6 mm)		
Weight:	.5oz (14g)		

Quality Standards & Approvals

Certifications:	"-A" models UL497A "-B" models UL497B
Warranty:	10 Year Limited Warranty



 2345 • www.diteksurgeprotection.com

SPS-100056-001 Rev 7 06/21

Every precaution has been taken to ensure that this literature is accurate and complete. DITEK Corporation assumes no responsibility and disclaims all liability for damages resulting from the use of this information or for any errors or omissions.