



DTK-S Series

66 Block Surge Protectors

DITEK's **DTK-S Series** quick-connect surge protectors are designed specifically for Voice/Data professionals. The Snap-It provides both voltage and current limiting in addition to surge protection. Available in four different voltages, the DTK-S series makes digital line protection a "snap!"



PRODUCT FEATURES

- Quick connect module – no bridge clips required
- Each Snap-It protects one pair
- Field-replaceable, with built in diagnostic test points
- Small form factor reduces installation space requirements
- Requires (1) DTK-SIGB ground bar per 66 block

APPLICATIONS

- Digital Voice/Data Systems
- Intercom Systems
- Analog Phone Systems

ACCESSORIES

- DTK-SIGB

TECHNICAL SPECIFICATIONS				
DTK-S	14B	30B	50B	130B
Service Voltage:	14Vdc	30Vdc	50Vdc	130Vdc
MCOV:	24V	48V	64V	150V
Clamping Voltage:	29V	59V	76V	167V
Wiring Configuration:	1 pair			
Protection Modes:	Differential Mode (L-L) Common Mode (L-G)			
Surge Current Rating:	5,000A			
Max. Continuous Current:	2 amps			

DITEK Surge Protection, Largo, FL 33771 • Sales: 800-753-2345
Diteksurgeprotection.com • SPS-100056-001 Rev 9 05/26





DTK-S Series

66 Block Surge Protectors

MECHANICAL SPECIFICATIONS	
Connection Method:	66 block snap-on
Housing:	ABS
Operating Temperature:	-40°F – 158°F (-40°C – 70°C)
Maximum Humidity:	95% non-condensing
Dimensions:	3.24 in. L x 0.38 in. W x 1.56 in. H (82 mm x 10 mm x 40 mm)
Weight:	0.5 oz (14g)

SAFETY STANDARDS AND CERTIFICATIONS	
Certifications:	UL 497B
Standards Compliance:	RoHS
Warranty:	10 Year Limited Warranty

