

DTK-SL "Snap-Lite" Series 66 Block Quick-Connect Surge Protectors

DITEK's "Snap-It" Series quick—connect surge protectors are designed specifically for Voice/Data professionals. The Snap-Lite provides both voltage and current limiting in addition to surge protection. The unique multi-function diagnostic LED shows protection status, line continuity and line usage. Available in four different voltages, there is a Snap-Lite for virtually any analog 66 block application.



Product Features

- Quick connect module no bridge clips required
- > LED diagnostic indicator
- > Each Snap-It protects one pair
- > Field-replaceable module
- Self-resetting fuse on models with "A" suffix
- Models available for both current-limited and standard lines

Applications

Analog Voice/Data Systems

Note

Each 66 Block requires one ground bar: DTK-SIGB



Technical Specifications				
DTK-	SL30	SL50	SL95	SL130
Service Voltage:	30V	50V	95V	130V
MCOV:	38V	66V	127V	175V
Clamping Voltage:	47V	82V	150V	204V
Protection Modes:	Tip-Ground, Ring-Ground			
Surge Current Rating:	1,000A	3,500A	3,500A	3,500A
Max. Continuous Current:	"-A" models 150mA "-B" models 2A			

Mechanical Specifications			
Base Connection Method:	Press-to-Fit connection to 66 Block		
Housing:	High Impact Plastic		
Operating Temperature:	-40°F - 158°F (-40°C - 70°C)		
Maximum Humidity:	95% non-condensing		
Dimensions:	.3.24" L x .38" W x 1.56" H (82.3 mm x 9.6 mm x 39.6 mm)		
Weight:	.5oz (14g)		

Quality Standards & Approvals		
Certifications:	"-A" models UL497A "-B" models UL497B	
Warranty:	10 Year Limited Warranty	





