



DTK-SL “Snap-Lite” Series 66 Block Quick-Connect Surge Protectors

DITEK’s “Snap-Lite” Series quick-connect surge protectors are designed specifically for Voice/Data professionals. The Snap-Lite provides both voltage and current limiting in addition to surge protection. The unique multi-function diagnostic LED shows protection status, line continuity and line usage.



Product Features

- Quick connect module – no bridge clips required
- LED diagnostic indicator
- Each Snap-It protects one pair
- DTK-SIGB ground bar required for installation

Applications

- Analog Voice Systems
- 25v Intercom Speaker

Note

- Each 66 Block requires one ground bar: DTK-SIGB



Technical Specifications

DTK-	SL30B	SL130B
Service Voltage:	30V	130V
MCOV:	48V	150V
Clamping Voltage:	59V	167V
Protection Modes:	Tip-Ground, Ring-Ground	
Surge Current Rating:	5,000A	
Max. Continuous Current:	2 Amps	

Mechanical Specifications

Base Connection Method:	Press-to-Fit connection to 66 Block
Housing:	High Impact Plastic
Operating Temperature:	-40°F - 158°F (-40°C - 70°C)
Maximum Humidity:	95% non-condensing
Dimensions:	3.24" L x .38" W x 1.56" H (82.3 mm x 9.6 mm x 39.6 mm)
Weight:	.5 oz (14g)

Quality Standards & Approvals

Certifications:	UL497B
Warranty:	10 Year Limited Warranty

