



# DTK-SL Series

66 Block Surge Protectors

**DITEK's DTK-SL Series** quick-connect surge protectors are designed specifically for Voice/Data professionals. The Snap-Lite provides both voltage and current limiting in addition to surge protection. The unique multi-function diagnostic LED shows protection status, line continuity and line usage.



## PRODUCT FEATURES

- Quick connect module – no bridge clips required
- Each Snap-It protects one pair
- LED diagnostic indicator
- Small form factor reduces installation space requirements
- Requires (1) DTK-SIGB ground bar per 66 block

## APPLICATIONS

- 25V Intercom Speakers
- Analog Phone Systems

## ACCESSORIES

- DTK-SIGB

TECHNICAL SPECIFICATIONS		
DTK-SL	30B	130B
Service Voltage:	30Vdc	130Vdc
MCOV:	48V	150V
Clamping Voltage:	59V	167V
Wiring Configuration:	1 pair	
Protection Modes:	Differential Mode (Line-Line) Common Mode (Line-Ground)	
Surge Current Rating:	5,000A	
Max. Continuous Current:	2 amps	





# DTK-SL Series

66 Block Surge Protectors

MECHANICAL SPECIFICATIONS	
Connection Method:	66 block snap-on
Housing:	ABS
Operating Temperature:	-40°F – 158°F (-40°C – 70°C)
Maximum Humidity:	95% non-condensing
Dimensions:	3.24 in. L x 0.38 in. W x 1.56 in. H (82 mm x 10 mm x 40 mm)
Weight:	0.5 oz (14g)

SAFETY STANDARDS AND CERTIFICATIONS	
Certifications:	UL 497B
Standards Compliance:	RoHS
Warranty:	10 Year Limited Warranty

