


DTK-SW8PL

8-Port Gigabit Ethernet PoE+ Switch



DITEK's DTK-SW8PL 8-Port Gigabit Ethernet PoE+ Switch with 2 RJ45 Uplinks and LCD Screen passes both data and electrical power to a number of PoE-compatible devices using existing infrastructure cabling.

Product Features

- Provides power and data for up to 8 PoE network devices
- 10/100/1000 auto-sensing ports for automatic detection of optimal network speeds
- Manual extend mode reduces network speed and extends PoE support to 250 m
- Green Ethernet power saving technology deactivates unused ports and adjusts power levels
- Power output up to 30 watts per port
- PoE power budget of 130 watts
- All RJ ports equipped with Auto-MDIX and auto-negotiation support
- Supports up to 8192 MAC address entries
- Cooling fan for ventilation
- Provides private VLAN (port isolation) functionality

Applications

- VoIP PoE Phone
- Wireless PoE Access Point
- PoE Network Camera

Package Contents

- 8-Port Gigabit Ethernet PoE+ Switch with 2 RJ45 Uplink Ports and LCD Screen
- Power Cable
- User Manual
- 19" Mounting Brackets

Technical Specifications

Backplane Speed:	20 Gbps
Switch Architecture:	Store and Forward

Power

Input:	100 – 240 VAC 50 – 60 Hz, 2.5 A
PoE Budget:	130 Watts (maximum)
Power Consumption:	140 Watts (maximum)

Display

Type:	LCD
Resolution:	128 x 64 pixels
Viewing Area:	43 mm x 23 mm (1.69" x 0.9")

Environmental

Housing:	Metal Case
Dimensions:	11.06"L x 7.09"W x 1.75"H (280.92mm x 180.09mm x 44.45mm)
Weight:	5.38lbs. (2.44kg)
Operating Temperature:	0-45°C (32-113°F)
Operating Humidity:	10-90% RH, non-condensing
Storage Temperature:	-10 - 70°C (14-158°F)

Standards & Approvals

Certifications:	FCC Class A, CE, RoHS
Standards Compliance:	IEEE 802.3 (10Base-T Ethernet) IEEE 802.3ab (Twisted Pair GbE) IEEE 802.3af (PoE 802.3at Type 1) IEEE 802.3at (PoE 802.3at Type 2) IEEE 802.3az (Energy Efficient Ethernet) IEEE802.3u (100Base-TX Fast Ethernet) IEEE 802.3x (Flow Control Full Duplex)
Warranty:	3 Year Limited

