



# DTK-UPS Series

Line Interactive Uninterruptible Power Supplies



**DITEK's DTK-UPS Series** 600VA and 1000VA models are designed to provide clean and stable power to connected equipment utilizing the built-in AVR stabilizer, while its embedded microprocessor control guarantees exceptional reliability. All outlets on each model provide backup power to critical equipment.

## PRODUCT FEATURES

- Compliant to U.S. DOE Energy Conservation Standard efficiency requirements (Jan 2022)
- Provides a comprehensive backup power solution in a small, economic package
- Built-in protection for an Ethernet circuit
- Embedded microprocessor control guarantees exceptional reliability
- Built-in boost and buck AVR for voltage stabilization
- Touch screen LCD to rotate through display information
- Auto-restart while AC is recovering
- Off-mode charging
- Cold start function
- USB connection for software download

## APPLICATIONS

- Home and Office Workstations
- POS Terminals
- Small Phone Systems
- Home Theater Systems

DITEK Surge Protection, Largo, FL 33771 • Sales: 800-753-2345  
Diteksurgeprotection.com • SPS-100019-001 Rev 6 05/26





# DTK-UPS Series

Line Interactive Uninterruptible Power Supplies

TECHNICAL SPECIFICATIONS		
Part Number:	<b>DTK-UPS600</b>	<b>DTK-UPS800</b>
Capacity:	600VA / 360W	1000VA / 600W
<b>INPUT</b>		
Input Voltage:	110/120Vac	
Voltage Range:	81-145Vac	
Frequency Range:	50/60Hz (Auto-sensing)	
<b>OUTPUT</b>		
Output Voltage:	110/120Vac	
AC Voltage Regulation:	Battery mode: +/- 10%	
Frequency Range:	Battery mode: 50Hz or 60Hz +/- 1Hz	
Transfer Time:	2ms - 6ms	
Waveform (Battery Mode):	Simulated sinewave	
Number of Outlets:	6 (UPS)	8 (UPS)
<b>BATTERY</b>		
Battery Type & Quantity:	12Vdc / 7Ah x 1	12Vdc / 7Ah x 2
Battery Run Time:	19 minutes @ 25% load	21 minutes @ 25% load
Typical Recharge Time:	4-6 hours recover to 90% capacity	
<b>PROTECTION &amp; INDICATORS</b>		
Full Protection:	Battery Mode: Every 10 seconds Low Battery: Every second Overload: Every 0.5 seconds Fault: Continuous	
LCD:	Input Voltage, Output Voltage, Battery, Load	
Alarm Sounding:		
<b>PHYSICAL &amp; ENVIRONMENTAL</b>		
Dimensions:	11.0 in. L x 4.0 in. W x 5.6 in. H (279 mm x 101 mm x 142 mm)	12.6 in. H x 5.1 in. W x 7.2 in. H (320 mm x 130 mm x 182 mm)
Weight:	10 lbs. (4.54 kg)	18.5 lbs. ( 8.39 kg)
Humidity:	0-90% relative humidity @ 0-40°C (non-condensing)	
Noise Level:	Less than 40dB	
<b>SAFETY STANDARDS &amp; CERTIFICATIONS</b>		
Certifications:	UL 1778-2014 CSA C22.2 No.107.3-2014	
U.S. DOE Compliance:	Yes	
Overall Efficiency:	> 98.4%	

